

H 5293 US
11.06.2001

METHOD AND INSTRUMENT FOR MICROSCOPY

CROSS REFERENCE TO RELATED APPLICATIONS

This invention claims priority of the German patent applications
100 30 013.8 and 101 15 487.9 and 101 15 589.1 and 101 15 486.0 and 101 15
5 488.7 and 101 15 509.3 and 101 15 577.8 and 101 15 590.5 which are
incorporated by reference herein.

Sub A17
10 This application refers to US patent application "ARRANGEMENT FOR
STUDYING MICROSCOPIC PREPARATIONS WITH A SCANNING
MICROSCOPE", (Attorney Docket 016790/0424, Leica Reference H5226US)
which is incorporated by reference herein.

This application refers to US patent application "ILLUMINATING DEVICE
AND MICROSCOPE", (Attorney Docket 016790/0427, Leica Reference
H5230US) which is incorporated by reference herein.

15 This application refers to US patent application "ENTANGLED-PHOTON
MICROSCOPE AND CONFOCAL MICROSCOPE", (Attorney Docket
016790/0242.), Leica Reference H5224US) which is incorporated by reference
herein.

20 This application refers to US patent application "ARRANGEMENT FOR
EXAMINING MICROSCOPIC PREPARATIONS WITH A SCANNING
MICROSCOPE, AND ILLUMINATION DEVICE FOR A SCANNING
MICROSCOPE", (Attorney Docket 016790/0422, Leica Reference H5164US)
which is incorporated by reference herein.

H 5293 US
11.06.2001

SUBA1
cont.

This application refers to US patent application "METHOD AND INSTRUMENT FOR ILLUMINATING AN OBJECT", (Attorney Docket 016790/0424, Leica Reference H5228US) which is incorporated by reference herein.

5 This application refers to US patent application "SCANNING MICROSCOPE WITH MULTIBAND ILLUMINATION AND OPTICAL COMPONENT FOR A SCANNING MICROSCOPE WITH MULTIBAND ILLUMINATION", (Attorney Docket 016790/0423, Leica Reference H5222US) which is incorporated by reference herein.

10 This application refers to US patent application "SCANNING MICROSCOPE", (Attorney Docket 016790/0429, Leica Reference H5232US) which is incorporated by reference herein.

FIELD OF THE INVENTION

The invention relates to a method for illuminating an object. The invention also relates to an instrument for illuminating an object.

15 BACKGROUND OF THE INVENTION

Laid-open patent specification DE 198 53 669 A1 discloses an ultrashort-pulse source with controllable multiple-wavelength output, which is used especially in a multiphoton microscope. The system has an ultrashort-pulse laser for producing ultrashort optical pulses of a fixed wavelength and at least one
20 wavelength conversion channel.

Patent US 6,097,870 discloses an arrangement for generating a broadband spectrum in the visible and infrared spectral range. The arrangement is based on a microstructured fibre, into which the light from a pump laser is injected. The pump light is broadened in the microstructured fibre by non-linear effects. So-

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

5

10

15

20

25

Microspot arrays or so-called microplates are used in genetic, medical and

biodiagnosis for studying large numbers of specifically labelled spots, which are preferably applied in a grid. A microplate reader which can be adjusted both in excitation wavelength and in detection wavelength is disclosed in the European Patent Application EP 0 841 557 A2.

- 5 The illumination methods and illuminating instruments known from the prior art have several disadvantages. The known broadband illuminating instruments mostly have a low luminance compared with laser-based illuminating devices, whereas the latter provide the user only with discrete wavelength lines whose spectral position and width can be adjusted only to a small extent, if at all. Owing
10 to this limitation of the working spectrum, the known illuminating devices are not flexibly usable. Laser-based illuminating devices and illuminating methods also have the disadvantage that, owing to the high coherence of the laser light, disruptive interference phenomena, such as e.g. diffraction rings and Newton's rings, occur. To reduce these interference effects, additional optical elements are
15 often used, which reduce the light power by intrinsic absorption and by scattering.

SUMMARY OF THE INVENTION

- It is an object of the invention to provide a method for illuminating an object which is universally usable and flexible, furthermore provides a broad wavelength spectrum together with a high luminance, and also minimizes
20 interference phenomena.

The object is achieved by a method for illuminating an object comprising the following steps:

- generating a light beam with a laser,
- injecting a light beam into a microstructured optical element which spectrally
25 broadens the light of the light beam,

- shaping the spectrally broadened light beam to form an illumination light beam,
and

- directing the illumination light beam onto the object.

5 It is another object of the invention to specify an instrument for illuminating an object, which is universally usable and flexible, furthermore provides a broad wavelength spectrum together with a high luminance, and also minimizes interference phenomena.

10 The object is achieved by an Illuminating instrument comprising: a laser that emits a light beam, a microstructured optical element that spectrally broadens the light from the laser and an optical means for shaping the spectrally broadened light into an illumination light beam.

15 It is another object of the invention to specify a device for a microscopic inspection of an object, which is universally usable and flexible, furthermore provides a broad wavelength spectrum together with a high luminance, and also minimizes interference phenomena.

The object is achieved by a device comprising: a laser that emits a light beam, a microstructured optical element that spectrally broadens the light from the laser and an optical means for shaping the spectrally broadened light into an illumination light beam.

20 The invention has the advantage that it is universally usable, easy to handle and flexible, and furthermore provides illumination with light from a wide wavelength range. The light also has very low coherence, so that disruptive interference phenomena are avoided.

25 By using microstructured fibres, as described in the previously mentioned US patent 6,097,870 or in the publication by Birks et al., a broad continuous wavelength spectrum is accessible. Arrangements of the disclosed type, however,

11.06.2001 15:50:00

are difficult to handle, inflexible and susceptible to interference, especially because of the complexity of the individual optical components and their relative adjustment.

5 A configuration variant in which a lens, which shapes the spectrally broadened light into a beam, is arranged downstream of the microstructured optical element, is especially advantageous. This lens is preferably located inside a casing which houses the entire instrument, immediately in front of or in a light exit opening. The lens is preferably a variable lens with which various divergent, collimated or convergent beam shapes can be produced.

10 All common laser types may be used as the laser. In a preferred configuration, the laser is a short-pulse laser, for example a mode-locked solid-state laser, which emits light pulses with a pulse width of from 100 fs to 10 ps. The wavelength of the laser is preferably matched to the "zero dispersion wavelength" of the fibre, or vice versa. Apparently, the zero dispersion wavelength can be "shifted" over a
15 certain wavelength range, and this needs to be taken into account when pulling the fibre.

An embodiment of the illuminating device which contains an instrument for varying the power of the spectrally broadened light is especially preferred. In this case, it is more particularly advantageous to configure the illuminating device in
20 such a way that the power of the spectrally broadened light can be varied or can be fully stopped-out with respect to at least one selectable wavelength or at least one selectable wavelength range.

An instrument for varying the power of the spectrally broadened light is preferably provided. Examples are acousto-optical or electro-optical elements,
25 such as acousto-optical tunable filters (AOTFs). It is likewise possible to use dielectric filters or colour filters, which are preferably arranged in cascade. Particular flexibility is achieved if the filters are fitted in revolvers or in slide mounts, which allow easy insertion into the beam path of the spectrally broadened

light.

A configuration which makes it possible to select at least one wavelength range from the spectrally broadened light, the light of the selected wavelength range being directed onto the object, is more particularly advantageous. This can be
5 done, for example, using an instrument which spectrally resolves the spectrally broadened light in a spatial fashion, in order to make it possible to suppress or fully stop-out spectral components with a suitable variable aperture arrangement or filter arrangement, and subsequently recombine the remaining spectral components to form a beam. A prism or a grating, for example, may be used for
10 the spatial spectral resolution.

In a special configuration, the method according to the invention comprises the further step of adjusting the power of the spectrally broadened light. To vary the power of the spectrally broadened light, in another alternative embodiment, a Fabry-Perot filter is provided. LCD filters can also be used.

15 In a more particularly preferred configuration variant, the illuminating method comprises the additional step of adjusting the spectral composition of the spectrally broadened light.

An embodiment which directly has an operating element for adjusting the light power and the spectral composition of the spectrally broadened light, is especially
20 advantageous. This may be a control panel or a PC. The adjustment data is preferably transmitted in the form of electrical signals to the illuminating instrument, or to the instrument for varying the power of the spectrally broadened light. Adjustment using sliders, which are displayed on a PC monitor and, for example, can be operated using a computer mouse, is particularly clear.

25 According to the invention, it has been discovered that the divergence of the light injected into the microstructured optical element has a considerable influence on the spectral distribution of the spectrally broadened light. In a particularly preferred and flexible configuration, the illuminating instrument contains a

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

Since the spectral distribution of the spectrally broadened light depends on the polarization and the wavelength of the light injected into the microstructured optical element, in a particular configuration, instruments are provided for adjusting and influencing these parameters. In the case of lasers, which emit linearly polarized light, a rotatably mounted $\lambda/2$ plate is used to rotate the polarization plane. Somewhat more elaborate, but also more flexible, is the use of a Pockels cell, which also makes it possible to set any desired elliptical polarization, or of a Faraday rotator. To adjust the wavelength, a birefringent plate or a tiltable etalon is preferably provided in the laser.

In a particular configuration, an instrument is provided which permits analysis of the broadened-wavelength light, in particular with regard to the spectral composition and the luminance. The analysis instrument is arranged in such a way that part of the spectrally broadened light is split off, for example with the aid of a beam splitter, and fed to the analysis instrument. The analysis instrument is preferably a spectrometer. It contains, for example, a prism or a grating for the spatial spectral resolution, and a CCD element or a multichannel photomultiplier as the detector. In another variant, the analysis instrument contains a multiband detector. Semiconductor spectrometers can also be employed.

To establish the power of the spectrally broadened light, the detectors are configured in such a way that an electrical signal, which is proportional to the light power and can be evaluated by electronics or a computer, is generated.

25 The embodiment which contains a display for the power of the spectrally broadened light and/or for the spectral composition of the spectrally broadened light is more particularly advantageous. The display is preferably fitted directly on the casing or to the control panel. In another embodiment, the monitor of a PC is

used for displaying the power and/or the spectral composition.

In another configuration, the method according to the invention comprises the step of adjusting the polarization of the spectrally broadened light. To that end, a rotatably arranged polarization filter, a $\lambda/2$ plate, a Pockels cell or a Faraday rotator is provided.

In a very preferred embodiment, the laser is a pulse laser which preferably emits light pulses with a pulse energy in excess of 1 nJ. In relation to this configuration, the method according to the invention comprises the additional step of adjusting the pulse width of the spectrally broadened light. It is furthermore advantageous that the method allows the further step of adjusting the chirp of the spectrally broadened light. Using these additional steps, the pulse properties of the light directed onto the object can be matched individually to the object in question. "Chirp" means the time sequence of the light are different wavelengths within a pulse. To that end, the instrument according to the invention preferably comprises a prism or a grating arrangement which, in a more preferred configuration, is combined with an LCD strip grating. Arrangements for varying the pulse width and the chirp are adequately known to a person skilled in the art.

The illuminating method and instrument can be used, particularly to illuminate a microscopic object, in particular in a microscope, a video microscope, a scanning microscope or confocal scanning microscope. It is more particularly advantageous if the wavelength of the light directed onto the object, in the case of fluorescence applications or applications which are based on Förster transfer, is matched accurately to the excitation wavelength of the fluorochromes present in the object.

The illuminating method and instrument can also be used very particularly advantageously in endoscopy, flow cytometry and lithography.

In a preferred configuration of the scanning microscope, the microstructured optical element is constructed from a plurality of micro-optical structure elements, which have at least two different optical densities. A configuration in which the

optical element contains a first region and a second region, the first region having a homogeneous structure and a microstructure comprising micro-optical structure elements being formed in the second region, is more particularly preferred. It is furthermore advantageous if the first region encloses the second region. The
5 micro-optical structure elements are preferably cannulas, webs, honeycombs, tubes or cavities.

In another configuration, the microstructured optical element consists of adjacent glass or plastic material and cavities. A particularly preferred alternative embodiment is one in which the microstructured optical element consists of
10 photonic band gap material and is configured as an optical fibre. An optical diode, which suppresses back-reflections of the light beam due to the ends of the optical fibre, is preferably arranged between the laser and the optical fibre.

A more particularly preferred alternative embodiment, which is simple to implement, contains a conventional optical fibre having a fibre core diameter of
15 approximately 9 μm , which has a taper at least along a subsection, as the microstructured optical element. Optical fibres of this type are known as so-called "tapered fibres". The optical fibre preferably has an overall length of 1 m and a taper over a length of from 30 mm to 90 mm. The diameter of the optical fibre, in a preferred configuration, is approximately 2 μm in the region of the taper. The
20 fibre core diameter is correspondingly in the nanometre range.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject-matter of the invention is diagrammatically represented in the drawing and will be described below with the aid of the figures, in which:

- Fig. 1 shows a flow chart of the method according to the invention,
25 Fig. 2 shows an illuminating device according to the invention with a power

meter and a display,

Fig. 3 shows, as an example, the use of an instrument according to the invention in a confocal scanning microscope,

Fig. 4 shows an embodiment of the microstructured optical element, and

5 Fig. 5 shows another embodiment of the microstructured optical element.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 shows a flow chart of the method according to the invention. In a first step, the light from a laser is injected 1 into a microstructured optical element that spectrally broadens the light. In this case, the light is guided to the
10 microstructured optical element, for example with the aid of mirrors, and is preferably focused onto the microstructured optical element using a variable lens. In a second step, the light emerging from the microstructured optical element is shaped 3 to form an illumination light beam, preferably with the aid of optical means which are configured as lens systems. In a further step, the illumination
15 light beam is directed 5 onto the object.

Fig. 2 shows an illuminating instrument 7 which contains a laser 9 that is embodied as a mode-locked Ti:sapphire laser 11 and emits a light beam 13, which is shown in dashes, with the property of an optical pulse train. The width of the light pulses is approximately 100 fs with a repetition rate of approximately
20 80 MHz. The light beam 13 is focused by the optical means 15, which is configured as a zoom lens 17 and is arranged displaceably along the propagation direction of the light beam, onto a microstructured optical element 19. The microstructured optical element 19 consists of an optical fibre 23 having a taper 21. In the microstructured optical element, the light from the laser is spectrally
25 broadened. All the components are located in a casing 25 having a light exit opening 27, through which the illumination light beam 29 leaves the casing 25 as

a divergent beam. The spectrum of the spectrally broadened light 31 extends from approximately 300 nm to 1600 nm, the light power being substantially constant over the entire spectrum. The spectrally broadened light 31 emerging from the optical fibre 23 is shaped with the aid of the lens 33 to form the collimated illumination light beam 29. Using the beam splitter 35, a subsidiary light beam 37 of the illumination light beam 29 is split off and diverted onto an analysis instrument 39. The latter contains a prism 41 which spectrally spreads the subsidiary light beam 37 in a spatial fashion to form a light cone 43 that diverges in the spreading plane, and a photodiode linear array 45 for detecting the light. The photodiode linear array 45 generates electrical signals, which are proportional to the power of the light of the spectral range in question and are fed to a processing unit 47. The latter is connected to a PC 49, on whose monitor 51 the spectral composition is displayed in the form of a graph 53 within a coordinate system having two axes 55, 57. The wavelength is plotted against the axis 55 and the power of the light is plotted against the axis 57. Clicking the graph 53 using a computer mouse 59 and moving the computer mouse 59 at the same time generates a dotted graph 61, which can be deformed in accordance with the movement of the computer mouse 59. As soon as the computer mouse 59 is clicked again, the computer 49 drives an instrument for varying the power 63 in such a way as to produce the spectral composition preselected by the dotted graph 61. The instrument for varying the power 63 of the spectrally broadened light 31 is designed as an AOTF 65 (acousto-optical tunable filter), and is configured in such a way that the wavelengths are influenced independently of one another, so that the spectral composition of the spectrally broadened light 31 can be adjusted. A system for controlling the output power of the laser 9 by means of the computer is furthermore provided. The user makes adjustments with the aid of the computer mouse 59. A slider 67, which is used for adjusting the overall power of the spectrally modified light 31, is represented on the monitor 51.

Fig. 3 represents, as an example, the use of an instrument according to the invention in a confocal scanning microscope 69. The illumination light beam 29

coming from the illuminating instrument 7 is reflected by a beam splitter 71 to the scanning module 73, which contains a cardan-suspended scanning mirror 75 that guides the light beam 29 through the microscope lens 77 and over or through the object 79. In the case of non-transparent objects 79, the illumination light beam 29 is guided over the object surface. In the case of biological objects 79 or transparent objects 79, the illumination light beam 29 can also be guided through the object 79. This means that various focal planes of the object 79 are illuminated successively by the illumination light beam 29, and are hence scanned. Subsequent combination then gives a three-dimensional image of the object 79.

10 The light beam 29 coming from the illuminating instrument 7 is represented in the figure as a solid line. The light 81 leaving the object 79 travels through the microscope lens 77 and, via the scanning module 73, to the beam splitter 71, then it passes through the latter and strikes the detector 83, which is embodied as a photomultiplier. The light 81 leaving the object 79 is represented as a dashed line.

15 In the detector 83, electrical detection signals proportional to the power of the light 81 leaving the object 79 are generated and processed. The illumination pinhole 85 and the detection pinhole 87, which are normally provided in a confocal scanning microscope, are indicated schematically for the sake of completeness. For better clarity, however, a few optical elements for guiding and

20 shaping the light beams are omitted. These are adequately known to a person skilled in this field.

Fig. 4 shows an embodiment of the microstructured optical element 19. It consists of photonic band gap material, which has a special honeycombed microstructure 89. The honeycombed structure that is shown is particularly suitable for generating broadband light. The diameter of the glass inner cannula 91 is approximately 1.9 μm . The inner cannula 91 is surrounded by glass webs 93. The glass webs 93 form honeycombed cavities 95. These micro-optical structure elements together form a second region 97, which is enclosed by a first region 99 that is designed as a glass cladding.

The invention has been described with reference to a particular embodiment. It is, however, obvious that modifications and amendments may be made without thereby departing from the scope of protection of the following claims.